Mindluster Platform

About the course Getting Started with Flexbox

To make an element into a grid container, we need to use either the display: grid; or the display: inline-grid; property. The former results in a block-level grid, while the latter leads to an inline-level grid. In the CSS, we use the display: grid; property on the . container element to create a block-level CSS Grid .

Programming Category's Courses

Course Lesson(12)

Lesson 1 : **CSS Layouts Flexbox vs Grid vs Float**

Lesson 2 : **Getting Started with Flexbox**

Lesson 3 : **Replacing Float with Flexbox in Nav Menus**

Lesson 4 : **Responsive Forms with Flexbox and Media Queries**

Lesson 5 : **Intro to CSS Grid**

Lesson 6 : **CSS Grids Named Grid Areas**

Lesson 7 : **CSS Grids with Unequal Columns**

Lesson 8 : **CSS Grid and Positioning Elements**

Lesson 9 : **Overlapping CSS Grid Elements**

Lesson 10 : **Centering Anything with CSS**

Lesson 11 : **CSS Grid and grid auto flow**

Lesson 12 : **Two Layouts with the Same HTML**

Related courses

React Projects Workshops

Node js back end JavaScript

Python programming language

Social Network Theme UI With Sass

Full Stack React Django

Build a Node js App With Sequelize

for Business Contact
business@mindluster.com