Mindluster Platform

# About the course JENKINS Jenkins Beginners

You can also define Jenkins arguments via JENKINS_OPTS . This is useful for customizing arguments to the jenkins launcher in a derived Jenkins image. The following sample Dockerfile uses this option to force use of HTTPS with a certificate included in the image.

**Programming Category's Courses**

## Course Lesson(8)

Lesson 1 : **Jenkins Tutorial 1 Introduction to Jenkins | Basics of Jenkins CI**

Lesson 2 : **Jenkins Tutorial 2 Jenkins Installation and Setup | Configure Jenkins**

Lesson 3 : **Jenkins Tutorial 3 Jenkins Dashboard Overview | Homepage Overview**

Lesson 4 : **Jenkins Tutorial 4 Create First Job in Jenkins | Freestyle Job**

Lesson 5 : **Jenkins Tutorial 5 How to Parameterize Jenkins Job**

Lesson 6 : **Jenkins Tutorial 6 How to Run Automation Tests in Jenkins**

Lesson 7 : **Jenkins Tutorial 7 How to Parameterize Browser and URL in Jenkins**

Lesson 8 : **Jenkins Tutorial 8 Run Test Cases from Github using Jenkins**

## Related courses

**React Projects Workshops**

**Node js back end JavaScript**

**Python programming language**

**Social Network Theme UI With Sass**

**Full Stack React Django**

**Build a Node js App With Sequelize**

for Business Contact
business@mindluster.com